



*Clear,
Easy-to-read
Vacuum Fluorescent Display
Adjust the Height Freely*

- Supports 11 command modes included EPSON etc.
- Power supply from 5V to 24V to prevent any needless use of improper power input.
- OPOS/JPOS driver is standard
- 20-column x 2-line dot matrix in a wide viewing angle.
- Easy connectivity to a wide range of POS products.



Specification

General	Display Method	Vacuum Fluorescent Display (Blue-green)
	Number of characters	40 (20 coloums x 2 lines)
	Brightness	500~1000cd/m2
	Character font	5 x 7 dot matrix
	Character type	95 Alphanumeric, 32 International Characters
	Character size	9.02(H) x 5.25(W)mm
	Dot Size (XxY)	0.86 x 1.05mm
	Download characters	9 characters
	Panel Dimension	195(D) x 31.5(W) x 54(H)mm
	Pole Dimension	Per support length; 339(L) x 34(Dia)mm
	Base Dimension	139(D) x 119(w) x 24.5(H)mm
	Viewing Angle	Max. 135°
	Horizontal Rotation	Max. 355°
	Weight	Approx. 980 grams
Commands Mode		LD220, EPSON POS D101, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL
Language Support		FRANCE, GERMANY, U.K, DENMARK, SWEDEN, ITALY, SPAIN, JAPAN, NORWAY, SLAVONIC, RUSSIA, Portuguese, Canadian French, Nordic, Turkish, Greek West European Latin. CP858, CP860, WPC1252, CP857(TURKISH), polish, WPC1250, WPC1253(GREEK), WPC1255(Hebrew), WPC1251, CP866, CP852, CP737(DOSgreek), CP858, CP864(Arabic), Farsi(Iran)
Interface	Baud rate	RS-232(serial) / USB
Connection	MTBF	Direct connection 9600 or 19,200bps
Reliability	Consumption	30,000 hours
Power	EMC standards	5-24 VDC
Safety	Safety standards	FCC, CE, ROHS