TP805 3" Thermal Receipt Printer

- High printing speed up to 250mm/s
- Three-in-one interface, including RS232, Ethernet and USB
- Embedded with 2D barcode edition algorithm which supports the 2D barcode common in the market, such as QRcode/PDF417
- Provide Windows/Linux driver
- Provide complete OPOS driver
- Support page mode printing
- With double cash drawer driver
- Movable paper guard plate design which supports 58mm, 76mm, 80mm wide thermal paper







Metallic Printer Enclosure

Wide-range of Interfaces

Wall Mounted Kit

Specification







Power Supply	Input	AC 100V-240V 50-60HZ
	Output	DC 24V/2.5A
Paper	Paper Type	Thermal Receipt Paper
	Paper Width	58mm/80mm
	Paper Thickness	0.056~0.1mm
	Roll Paper Diameter	Max. OD ф83mm
	Paper Load	Easy paper loading
	Paper Cut	Partial cut
Environment	Operation	0°C~40°C, 20%~85%RH
	Storage	-20°C~70°C, 5%~95%RH
Physical	Dimension	195(L)x147(W)x147(H)mm
Characteristics Weight		1.8KG
Options & Accessories		USB/Serial/Parallel Cable, Paper
		Roll, Power Adapter, Power Cord,
		CD, Quick Start Guide
Software	Emulation	ESC/POS
	Driver	XP / Win7/Win8 /Win10/POSReady
		/Linux /OPOS
	SDK	WinCE, Win Mobile, Android, iOS















